

MG-980

MONTERO UNIVERSAL PACKING FOR ALL SORT OF PUMPS & VALVES

COMPOSICION




This packing is manufactured from a combination of high purity carbon filaments and pure expanded mineral graphite yarns from **GRAFOIL** with a corrosion inhibitor. It is diagonally braided to give a strong and homogeneous packing.

Packings produced solely from expanded graphite are weak and, where mechanical strenght is required for use in pumps or valves, the use of graphite filament braided anti-extrusion rings is recommended.

There are no such restrictions with MG-980. The incorporation of the carbon filament reinforcement at the corners enables this new, universal packing to be in both static and dynamic applications where the special thermal and chemical properties and the low coefficient of friction of graphite are needed.

MG-980 I- with Inconel core in the braid to improve its mechanical resistance.

PARAMETER

MG 980			
TEMPERATURE °C	600	600	600
PRESSURE (BAR)	200	75	35
VELOCITY (M/S)	1.5	2	30
PH	0-14	0-14	0-14

APPLICATIONS

Following types of **centrifugal pumps**: multistage, self-priming, positive displacement, slipt-casing, vertical and horizontal pumps, high pressure, submersible and axial-flow pumps.

Reciprocation and piston pumps

Other applications:
Pressure and dynamic equipment, turbines, compressors and, on the whole, every centrifugal movement at high speeds.

POWER & NUCLEAR PLANT.
CHEMICAL & PETROCHEMICAL INDUSTRIES
PULP & PAPERMILL.
SUGAR & FOOD INDUSTRIES.
CEMENT PLANT.
MARINE INDUSTRY.
STEEL & FOUNDRY INDUSTRY.



Montero®

FIBRAS Y ELASTOMEROS, S.A.

El Juncal, s/n. Edificio Fuentes 2º Local 11
48510 Valle de Trapaga, Vizcaya, España.
Tel. + 34-94 418 00 11 Fax. + 34-94 418 91 83
e-mail: access@monterofye.com
http://www.monterofye.com

The data given on this technical sheet should not be used as applications limits, but as guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

doce