

# MT-278

## COMPOSITION

This packing is constructed from crinkled and folded then lead foil around a non-asbestos graphited and lubricated core. Each core is additionally lubricated.

Material of construction: Lead foil, Alumina Silica Core, Mineral Lubricant, flake graphite.

Specially recommended for centrifugal pumps and oil handling, destilated, thermic fluids, abrasives and viscous (tar, and petroleum by-products), and fluids with crystallizing tendency.

## PARAMETER

MT-278	Maximum working conditions
TEMPERATURE (°C)	270
PRESSURE (Bar)	70
VELOCITY (m/s)	10
P-H	3-13



## APLICACIONES

Typical applications of this packing are centrifugal pumps, reciprocating steam rods and gasoline pumps.

Reciprocation and piston pumps

Other applications:  
 Pressure and dynamic equipment, turbines, compressors and, on the whole, every centrifugal movement at high pressures.

Pumps & equipment in:

POWER & NUCLEAR PLANT  
 PAPER & PULP MILL.  
 CHEMICAL & PETROCHEMICAL INDUSTRY.  
 SUGAR & FOOD INDUSTRY.  
 CEMENT PLANT.  
 STEEL & FOUNDRY FACTORIES.  
 MARINE INDUSTRY, etc.

**Montero®**

FIBRAS Y ELASTOMEROS, S.A.

El Juncal, s/n. Edificio Fuentes 2º Local 11  
 48510 Valle de Trapaga, Vizcaya, España.  
 Tel. + 34-94 418 00 11 Fax. + 34-94 418 91 83  
 e-mail: [access@monterofye.com](mailto:access@monterofye.com)  
<http://www.monterofye.com>

The data given on this technical sheet should not be used as applications limits, but as guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

